



# THE SSC CONTROLS COMPANY

PREMIER INDUSTRIAL CONTROLS

## Product Information Sheet

### G-Series Foot Switch with Front Gate

#### Design features:

- Available as an option for all standard G-Series models. Add "-GT" to end of any part number.
- Heavy-duty construction – ideal for tough industrial environments.
- 20 amp @ 125/250 VAC Honeywell® switches.
- Precise, adjustable switching action.
- 3/4"-14 N.P.T. threaded conduit entry.
- Powder-painted Safety Orange finish.
- Cast-iron base with cast-aluminum cover.
- 3- or 4-point mounting with optional 3M® bumper feet.

#### Quality features:

- Designed and manufactured under a quality system certified to ISO 9001 requirements.
- Includes a 1-year warranty on parts and labor.
- Made in USA of imported and domestic components.

**Dimensions (L x W x H):** 9.2" x 6.2" x 5.8"

**Weight:** 7.8 pounds


**Finish:** powder paint, safety orange

**Enclosure ratings:** IP-56; NEMA Type 2, 4, & 13



**Warning:** To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installing or removing this control.



Model	Action	Switches	Stages	Contacts*	Rating	Certifications
G500-MO-GT	Momentary	1	1	SPDT	20 amp, 125/250 VAC	 (Certified to CSA and UL standards)
G500-MA-GT	Maintained	1	1	SPDT	20 amp, 125/250 VAC	
G500-AT-GT	Anti-Trip	1	1	SPDT	20 amp, 125/250 VAC	
G502-MO-GT	Momentary	2	1	SPDT	20 amp, 125/250 VAC	
G502-MA-GT	Maintained	2	1	SPDT	20 amp, 125/250 VAC	
G502-AT-GT	Anti-Trip	2	1	SPDT	20 amp, 125/250 VAC	
G502-MO-2S-GT	Momentary	2	2	SPDT	20 amp, 125/250 VAC	
G502-AT-2S-GT	Anti-Trip	2	2	SPDT	20 amp, 125/250 VAC	

\*Note: Contacts are for each switch. Units with two switches may be adjusted either as DPDT circuitry or as two SPDT switches activating separately.

The SSC Controls Company  
 8909 East Avenue Mentor, Ohio 44060  
 Phone: 440 205-1600 Fax: 440 205-1700