



THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS


Product Information Sheet

DS100 and DS100-DG (Dual S-Series Foot Switch)

The DS100 consists of two S100 foot switches attached to a dual base, which connects the two units on a single platform. The DS100 is equipped with rubber bumper feet and can also be bolted to the floor. A single 4-conductor/ 16-gauge cable exits the unit and includes a green grounding lead. Ideal for lift tables, up/down or forward/ reverse position adjustment, and other applications. The DS100-DG adds a durable steel guard and removable bumper feet.

Design features:

- Durable steel base with powder-painted finish.
- Low profile ensures stability and ease-of-use.
- Equipped with two S100 foot switches.
- Heavy-duty cable with flexible strain relief.
- Non-slip 3M® traction pads or bumper feet.



Quality features:

- Designed and manufactured under a quality system certified to ISO 9001 requirements.
- Includes a 1-year warranty on parts and labor.
- Made in USA of foreign and domestic content.

Wiring (16/4 cable):
 Right switch – white & black leads
 Left switch – red & black leads
 Case ground – green lead



Model: DS100

Dimensions, L x W x H: 8" x 6" x 2"

Weight: 5.1 pounds

Finish: powder paint, black





Model: DS100-DG


Dimensions, L x W x H: 10.3" x 6.0" x 5.6"

Weight: 8.5 pounds

Finish: powder paint, safety orange

Model	Action*	Rating	Cord	Certification
DS100	momentary	13 amps @ 125/250 VAC	8-foot cable with leads	 
DS100-DG	momentary	13 amps @ 125/250 VAC	8-foot cable with leads	

*Momentary action: Press and hold to turn on, release to turn off. Both switches cannot be operated at the same time.

 **Warning:** To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.

The SSC Controls Company
 8909 East Avenue Mentor, Ohio 44060
 Phone: 440 205-1600 Fax: 440 205-1700