



THE SSC CONTROLS COMPANY

PREMIER INDUSTRIAL CONTROLS

Product Information Sheet

G503 Triple Switch (G-Series)

The G503 foot switch contains three switches inside each unit. The switches can be independently adjusted so they activate at separate times as the pedal is pressed down or at the same time. Designed for tough industrial and shop environments, the G-Series foot switches feature precise switching action, rugged cast-iron construction with a cast-aluminum cover, and user-friendly dimensions. Also available with a front gate, dual base, handle, and other options.

Design features:

- Heavy-duty construction – ideal for tough industrial environments.
- 20 amp @ 125/250 VAC Honeywell® switches.
- Each switch can be adjusted to activate separately or at the same time as the pedal is pressed down.
- Cast-iron base ensures stability.
- 3/4"-14 N.P.T. threaded conduit entry.
- Powder-painted Safety Orange finish.
- 3- or 4-point mounting with optional 3M® bumper feet.
- Oversized guard opening (5.5"H x 6"W).



Quality features:

- Designed and manufactured under a quality system certified to ISO 9001 requirements.
- Includes a 1-year warranty on parts and labor.
- Made in USA of imported and domestic components.



Dimensions (L x W x H): 9.2" x 6.2" x 5.5"

Weight: 7.6 pounds

Enclosure: IP-56; NEMA Type 2, 4 & 13

Finish: powder paint, safety orange



Warning: To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installing or removing this control.

Model	Action	Switches	Stages	Contacts, per Switch	Rating	Price	Wiring Diagram (TPDT)
G503-MO	Momentary	3	1	SPDT	20 amp, 125/250 VAC	\$122.90	
G503-MA	Maintained	3	1	SPDT	20 amp, 125/250 VAC	\$127.80	
G503-AT	Anti-Trip	3	1	SPDT	20 amp, 125/250 VAC	\$127.80	
G503-MO-2S	Momentary	3	2	SPDT	20 amp, 125/250 VAC	\$129.90	
G503-AT-2S	Anti-Trip	3	2	SPDT	20 amp, 125/250 VAC	\$132.40	

Note: Each switch can be adjusted independently to go off at the same time or at separate times as the pedal is pressed down.

The SSC Controls Company
 8909 East Avenue Mentor, Ohio 44060
 Phone: 440 205-1600 Fax: 440 205-1700