



# THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS®

## Product Information Sheet

### F-Series Foot Switches with Guards

The F-Series with Guards provide a tough powder-painted steel cover for any F-Series foot switch. The unit includes the foot switch enclosed in a tough 12-gauge steel guard. The guard provides a comfortable housing in which to locate the foot, as well as to protect the switch from debris.

#### Design features:

- Adds protection from debris and accidental actuation.
- Provides a secure location in which to position the foot.
- Cable cord grip is included (fits up to .60" cable diameter).
- Includes non-skid rubber bumper feet.
- Bolt-down holes included in the base.

#### Quality features:

- Designed and manufactured under a quality system certified to ISO 9001 requirements.
- Includes 1-year warranty.
- Made in USA of imported and domestic components.



#### Single-Unit Guard (F200-G shown)

Dimensions, L x W x H: 6.0" x 6.0" x 5.8"

Weight: 5.7 pounds

Finish: powder paint, safety orange




#### Dual-Unit Guard (DF200-DG shown)

Dimensions, L x W x H: 10.2" x 6.0" x 6.2"

Weight: 10.0 pounds

Finish: powder paint, safety orange

Model	Action	Electrical Rating, per Switch	Cert.
F200-G	Momentary	15 A, 1/2 HP, 125/250 VAC; SPDT	
F200-1501-G	Momentary	15 A, 1/2 HP, 125 VAC; includes cable with series tap plug	
F200-1502-G	Momentary	15 A, 1/2 HP, 125/250 VAC; includes cable with leads	
F300-G	Maintained	20 A, 125 VAC; 10 A, 250 VAC; SPST	
F500-G	Momentary	20A, 125/250 VAC; 1 HP, 125 VAC; 2 HP, 250 VAC; SPDT	
DF200-DG	Momentary	dual foot switch, each rated 15 A, 1/2 HP, 125/250 VAC, SPDT	
<p>Note: You can add a single guard to any F-Series foot switch simply by adding "-G" to the end of the model number (or any two units to a dual guard). See F-Series Product Information Sheet for more models.</p>			



**Warning:** To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.

The SSC Controls Company  
 8909 East Avenue Mentor, Ohio 44060  
 Phone: 440 205-1600 Fax: 440 205-1700