



# THE SSC CONTROLS COMPANY

THE FOOT SWITCH EXPERTS®

## Product Information Sheet

### F-Series Medium-Duty Foot Switch

Designed for a wide variety of applications, the F-Series Foot Switch features a tough die-cast zinc housing, attractive shape, easy wire hookup, and numerous switch / cable combinations.

#### Design features:

- Die-cast housing provides superior appearance and durability.
- Durable zinc alloy will not rust or easily break.
- Powder-painted black with bottom traction pad.
- Includes two exterior mounting holes for bolt-down option.
- Adjustable strain relief connector is included.
- Model F300 can be used to control lighting (push on / push off) and many other maintained-action applications.
- Model F222 (two stage) has an added force between each switch.



#### Quality features:

- Quality system certified to ISO 9001 requirements.
- Includes a 1-year warranty on parts and labor.
- Made in USA of imported and domestic components.




Model F200-1501 shown on left and F200-1502 on right.

Dimensions (L x W x H): 4.8" x 3.5" x 1.8"

Weight: 2.1 pounds (without cable)

Finish: powder paint

Enclosure rating: CSA Type 1; IEC IP-21



**Warning:** To avoid personal injury, do not use foot switches on machinery lacking effective point-of-operation safeguards. Disconnect input power before installation or maintenance.

Model	Action	Switches	Electrical Rating, per Switch*	Cable
F200	Momentary	1	15 A, ½ HP, 125/250 VAC	none
F200-1501	Momentary	1	15 A, ½ HP, 125 VAC	cable with plug for outlet
F200-1502	Momentary	1	15 A, ½ HP, 125/250 VAC	cable with leads
F202	Momentary	2	15 A, ½ HP, 125/250 VAC; DPDT	none
F222	Momentary, 2-Stage	2	15 A, 125/250 VAC; each stage SPDT	none
F300	Maintained	1	20 A, 125 VAC; 10 A, 250 VAC	none
F300-1501	Maintained	1	15 A, 125 VAC	cable with plug for outlet
F300-1502	Maintained	1	15 A, 125/250 VAC	cable with leads
F500	Momentary	1	20A, 125/250 VAC; 1 HP, 125 VAC; 2 HP, 250 VAC	none
F502	Momentary	1	10 A, 125/250 VAC (DPDT)	none
F540	Momentary	1	15 A, 125 VAC; 1 A, 125 VDC (SPDT-DB)	none

\*All switches have SPDT circuits except as noted. Units with cables are wired Normally Open (N.O.).

The SSC Controls Company  
8909 East Avenue Mentor, Ohio 44060  
Phone: 440 205-1600 Fax: 440 205-1700